

Presenting The World's First

Diet Cooler



Eats up less space. Eats less electricity

DiET by **Symphony**

DiET_{50T}

The world's tallest tower cooler comes to you with incredible energy efficiency at just 175 watts. With a powerful air throw of 35 feet, at high level too, Diet 50T cools up to 250 sq. ft. The cooler with the world's largest tank in its category, occupies very less floor space too.



Large tank capacity of 50 Litres / 13 Gallon (US)
No frequent refilling.



High Efficiency Pad
Cools 30% more than conventional pads.



Powerful 35 ft. Air Throw
Faster cooling and comfort.



Automatic Louvers
Better air distribution.



Multi Directional Wheels
Move effortlessly.



DiET_{22T}

The new Diet 22T is the perfect balance of performance and style. Power utilization of only 150 watts makes it one of the most energy efficient coolers in its category. Apart from accessorizing your home, it gives powerful cooling with a 30-ft air throw and cooling capacity of 200 sq. ft. Now, who's scared of summers?



Large tank capacity of 22 Litres / 5 Gallon (US)
Longer cooling time.



Powerful 30 ft. Air Throw
Faster cooling and comfort.



High Efficiency Pad
Cools 30% more than conventional pads.



Automatic Louvers
Better air distribution.



Multi Directional Wheels
Move effortlessly.



DiET_{8T}

The only sounds you hear while Diet 8T is functioning is your comments of appreciation. This hush cooler thrives on very little energy as well. But this sleek little powerhouse has an air throw of 25 feet and with an 8 litre tank capacity, cools up to 125 sq. ft. Don't the best things come in small packages?



Powerful 25 ft. Air Throw
Faster cooling and comfort.



High Efficiency Pad
Cools 30% more than conventional pads.



Automatic Louvers
Better air distribution.



Multi Directional Wheels
Move effortlessly.



Technical Specifications*

Parameters	Diet 50T	Diet 22T	Diet 8T
Cooling Area (Sq.m. / Sq.Ft.)	25 / 250	20 / 200	12.5 / 125
Air throw Distance (m. / Ft.)	11 / 35	9 / 30	7.5 / 25
Blower / Fan	Blower	Blower	Blower
Blower / Fan Diameter (mm / Inch)	180 / 7	180 / 7	180 / 7
Blower / Fan Speeds	Three	Three	Three
Motor RPM	1400	1400	1400
Air delivery (m ³ / hr. / CFM)	900 / 533	850 / 500	600 / 355
Electrical - 230V / 50-60 Hz			
Power Consumption (W)	175	150	125
Max. Current (A)	0.70	0.70	0.60
110V / 60 Hz			
Power Consumption (W)	210	190	170
Max. Current (A)	2.00	1.90	1.60
Water tank capacity (Ltrs./US Gallon)	50 / 13	22 / 5	8 / 2
Vertical louvers movement	Automatic	Automatic	Automatic
Ice chamber	Yes	Yes	Yes
Water inlet Top	Yes	Yes	Yes
Water inlet Back	Yes	Yes	Yes
Mosquito net / Dust filter	Yes	Yes	Yes
Water level indicator	Yes	Yes	Yes
Cooling media	Honeycomb /Celdek	Honeycomb /Celdek	Honeycomb /Celdek
Portability	Yes	Yes	Yes
Multi-directional wheels	Yes	Yes	Yes
Plastic motor mounting stand	Yes	Yes	Yes
Motor protection cover	Yes	Yes	Yes
Works on inverter	Yes	Yes	Yes
Product Dimensions (mm / Inch)			
Length	430 / 17	300 / 12	300 / 12
Breadth	360 / 14	330 / 13	330 / 13
Height	1345 / 53	895 / 35	730 / 29
Carton Dimensions (mm / Inch)			
Length	363 / 14	340 / 13	340 / 13
Breadth	415 / 16	350 / 14	350 / 14
Height	1310 / 52	920 / 36	755 / 30
Product Weight (Kgs. / lbs)	13 / 29	12 / 26	10 / 22
Product Weight (Incl. Packaging) (Kgs. / lbs)	17 / 37	14 / 31	13 / 29
Units per 40 ft. container (HC)	362	645	735

*Under test conditions, actuals may vary depending on the ambient conditions and the heat load. All specifications are approximate and may vary within $\pm 10\%$ of the specified value. All products are subject to continuous improvement. The company reserves the right to change specifications without any prior notice. Inverter has to be of appropriate rating and good quality.

