

## Ground Source Heat Pump (GSHP)

Model No: **GHP-20**

### Description

Our Geothermal Systems circulate water through pipes buried in the ground to extract the heat stored below the earth's surface. The average ground temperature just below the surface, in the UK is between 8°C and 13°C, this temperature remains constant throughout the year. The temperature of the water in the pipes is lower than the surrounding ground and so it warms up slightly. The returning water is chilled back down by the heat pump, where it is used to heat up a refrigerant. By compressing this 'warmed' refrigerant the temperature is further increased before being transferred to the building heating system. The heating water output from the heat pump is typically 45°C - 65°C.

### Features

- Japanese Inverter Technology
- Digital LED Controller
- Titanium Heat Exchange
- Oscillating air vanes for dissipation of cold air
- Auto Restart after power cut
- Intelligent Defrost
- Quiet Running
- Low Running Cost
- 80% More Efficient than Conventional Electric



### Specifications

Heating Output	20.4Kw
C.O.P. 20°C-50°C	≥5
Power Cont/Max A	8.6/10.4
Voltage	415
Water Output L/h	≥500
Noise dB(A)	≤58
Size (cm) (L/D/H)	100X65X60
Weight (Kg)	198



#### Head Office:

Martin Industries Ltd  
Unit 10  
Milton Business Centre  
Wick Drive  
New Milton  
Hampshire  
BH25 6RH  
UK

Tel: 0870 33 44 55 6

Fax: 0870 33 44 55 9

Email: [sales@airconditioningcentre.com](mailto:sales@airconditioningcentre.com)

Website: [www.airconditioningcentre.com](http://www.airconditioningcentre.com)