

Inverter Wall Split Systems

Our EASYfit split air conditioners comprises two elements - an internal and an external unit. The internal unit is fitted to a metal mounting plate on a wall in the room to be cooled, whilst the external unit is situated outside the building. The two are connected using copper pipe. The external unit, or condenser, removes the heat from the room and dissipates it outside, along with any condensation that's built-up in the system, whilst the internal unit provides cooling.

All our systems will Heat the room as well when required.



Features

- ▶ Remote control with luminous night-light
- ▶ A timer feature that will turn the unit on and off automatically
- ▶ Adjustable fan speeds for rapid cooling or minimum noise
- ▶ Heat-pump model provides heating as well as cooling
- ▶ High efficiency air filters to remove odours and particles
- ▶ Digital display to show operational settings and temperature



Specifications

Power Rating	220-240V / 50Hz
Capacity BTU/h (cooling)	12000 (3.5kW)
Capacity BTU/h (heating)	13000 (3.8kW)
Power Input W (C/H)	1060/1095
Current Input A (C/H)	4.6/4.5
EER (BTU/hr.w)	3.21
COP (w/w)	3.62
Noise dB(A)	32-42/54
Dehumidification (L/h)	1.2
Airflow (m3/h)	560
Net Dimension (mm) indoor (L/D/H)	800x190x280
Net Dimension (mm) outdoor (L/D/H)	795x255x540
Net Weight (kg) indoor	10
Net Weight (kg) outdoor	40
Max Room Size	25m sq
Max Conservatory Size	12m sq
Connecting Pipe Length Inc	4m

All ACC product's are guaranteed for 12 months (unless otherwise stated) from the date of original purchase.