

Inverter Ceiling Cassette System

Our EASYfit Inverter ceiling cassette air conditioner comprises three elements - two internal units and an external unit. The internal units are fitted into the ceiling in the room to be cooled, whilst the external unit is situated outside the building. The three are connected using copper pipe.

The external unit, or condenser, removes the heat from the room and dissipates it outside, along with any condensation that's built-up in the system, whilst the internal units providing cooling.

All our systems will Heat the room as well when required.



Features

- ▶ Remote control with luminous night-light
- ▶ A timer feature that will turn the unit on and off automatically
- ▶ Adjustable fan speeds for rapid cooling or minimum noise
- ▶ Heat-pump model provides heating as well as cooling
- ▶ High efficiency air filters to remove odours and particles
- ▶ Digital display to show operational settings and temperature

Specifications

Power Rating	220-240V / 50Hz
Rated capacity (kW) cooling/heating	7/8
Inverter capacity range (kW) cooling/heating	3.8-8.25/3.5-8.8
Rated power input (kW) cooling/heating	2.2/2.35
EER (W/W)	3.18
COP (W/W)	3.40
Indoor Unit 1	
Air flow volume (m ³ /h)	1145
ESP (Pa)	0
Noise level (dB(A))	48
Net weight (Kg)	28
Gross weight (Kg)	31
Dimension (L/D/H) (mm) Body/Grid	840x840x230/950x950x50
Packing dimension (L/D/H) (mm) Body/Grid	920x920x310/1030x1030x105
Control type (remote controller/wire controller)	Remote & Wire
Indoor Unit 2	
Air flow volume (m ³ /h)	1200
ESP (Pa)	45
Noise level (dB(A))	51
Net weight (Kg)	35
Gross weight (Kg)	39
Dimension (L/D/H) mm	930x530x260
Packing dimension (L/D/H) mm	995x595x320
Control type (remote/wire controller)	Remote & Wire
Outdoor Unit	
Compressor Qty	1
Compressor (Type/Brand)	Rotary/SANYO
Noise level (dB(A))	57
Net weight	55
Gross weight	60
Dimension (L/D/H)	1020x434x865
Packing dimension (L/D/H)	1030x440x960
Refrigerant	
Type	R410a
Charge	2300
Pipe size information	
Liquid pipe	6.35
Gas pipe	15.88
Tubing length	5
Max. Piping length (L1)	25
Max. Height IU under OU	10
Max. Height OU under IU	10

All ACC product's are guaranteed for 12 months (unless otherwise stated) from the date of original purchase.