Super Inverter Wall Split Systems

Our EASYfit split air conditioners comprises two elements - an internal and an external unit. The internal unit is fitted to a metal mounting plate on a wall in the room to be cooled, whilst the external unit is situated outside the building. The two are connected using copper pipe. The external unit, or condenser, removes the heat from the room and dissipates it outside, along with any condensation that's built-up in the system, whilst the internal unit provides cooling.



SPECIFICATIONS

Model	KFR23IW/X1CM-IU	
Power Rating (Ph-V-Hz)	220-240V / 50 Hz	
Capacity BTU/H (cooling) kW	9000 / 2.7	
Capacity BTU/H (heating) kW	9000 / 2.8	
Power Input (W) Cooling/Heating	910~920	
Current Input (A) Cooling/Heating	4.0~4.0	FEATURES
EER (BTU/hr.w)	SEER 5.5	
COP (W/W)	SCOP 3.4	
Dehumidification (L/h)	1	Adjustable
Indoor Noise Level dB(A) (Hi/M/Lo)	36/32/28	Heat-pum
Outdoor Noise Level dB(A)	NA	
Indoor Airflow (m3/h) (Hi/M/Lo)	400/350/320	Oscillating
Max. Current Rating (A) Fuse Rating (type D)	7.5	
Net Dimension (mm) indoor (W/D/H)	795x189x250	🗾 A timer fe
Net Dimension (mm) outdoor (W/D/H)	NA	
Net/Gross Weight (kg) indoor	6.5 / 8.5	High effic
Net/Gross Weight (kg) outdoor	NA	Anti-moul
Max Room Size (m²)	13-22	
Max Conservatory Size (m ²)	10	Digital dis
Connecting Pipe Length (m)	NA	
Pipe Diameter Liquid/Gas (Inch)	1/4 & 3/8	🗾 A "Smart
Selectable Temp Range °C	17-30	at the pus
Minimum Operating Temp (Cooling/Heating) °C	-7 / -15	
Automatic Restart after Power Failure	Yes	All our sy
Automatic Refrigerant Leak Detection & Self Diagnosis Systems	Yes	room as v

S

- le fan speeds for rapid cooling or minimum noise
- np model provides heating as well as cooling
- g air vanes for dissipation of cold air
- eature that will turn the unit on and off automatically
- ciency air filters to remove odours and particles
- uld coating for hygienic operation
- splay to show operational settings and temperature
- t Air" feature that will recall previous settings ish of a button

vstems will Heat the well when required.

All ACC product's are guaranteed for 12 months (unless otherwise stated) from the date of original purchase

